



Shut-off damper

A product line from Steinberg + Kirsch®

	SHUT-OFF DAMPER
Design	<ul style="list-style-type: none"> - Round or rectangular - Robust design - Low maintenance - Single or multi-vane
Size	- According to requirement
Tightness	- 99-99.9% area equivalent
Temperature	- Up to 1400°C
Drives	<ul style="list-style-type: none"> - Electric drive - Pneumatic actuator - Manual with hand wheel/lever
Damper modells	

Our shut-off dampers are used for the controlled opening and closure of lines, e.g. for the isolation of individual plant components during changeover operations, for the isolation of individual plant components during maintenance work and much more.

Examples of places where shut-off dampers are used are:

- Combustion system in waste incineration plants, biomass and other power plants.
- Air, steam and process gas ducting in process engineering
- Exhaust gas cleaning systems in power plants, waste incineration plants and the process industry

The selection of the correct shut-off dampers depends on various factors, such as type of medium to be controlled, pressure, temperature and other operating parameters.



**Please contact us
for more information!**

Rafael Moreno
Sales Engineer

T +41 76 512 47 73
moreno@energielink.ch

EnergieLink GmbH
Markgrafenstrasse 1
44623 Herne | Germany

T +41 56 511 03 33
F +41 56 511 03 38
info@energielink.eu
www.energielink.eu

EnergieLink
PLANT ENGINEERING & SOLUTIONS